For Residential and Light Commercial Applications

Job Name	Contractor
Job Location	Approval
Engineer	Contractor's P.O. No.
Approval	Representative

GAC Filter

Replacement Cartridges

Granular Activated Carbon (GAC) Cartridges

Sizes: 2³/₄" x 10", 2³/₄" x 20", 4¹/₂" x 10", and 4¹/₂" x 20"

GAC filters are an effective way of removing volatile compounds from drinking water for better tasting water. They are used to remove chlorine odor and taste from water. Polishing RO water with a Watts GAC cartridge improves its taste.

Specifications

Media	Water washed coconut shell granular activated carbon	
Minimum / Maximum Working Pressure	20psi / 125psi	
Minimum / Maximum Temperature	40°F / 100°F (4°C / 38°C)	
Maximum Flow Rate	1 GPM (9¾"), 3 GPM (4.5" x 9¾"), 5 GPM (4.5" x 20")	

PURE WATER



GAC Filters

Water Washed Coconut Shell Granular Activated Carbon Cartridges (GAC)

MODEL NO.	TYPE	0.D.	LENGTH	CAPACITY (GALS.)	NO. / CASE
PWFIL-GAC-STD-10X2.75-WW	GAC	23/4"	9¾"	2,500	24
PWFIL-GAC-STD-20X2.75-WW	GAC	23/4"	20"	5,000	24
PWFIL-GAC-BB-10X4.50-WW	GAC	4½"	9¾"	7,500	8
PWFIL-GAC-BB-20X4.50-WW	GAC	41/2"	20"	15,000	4

Note: Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.





A Watts Water Technologies Company