

For Residential and Light Commercial Applications

Job Name _____

Contractor _____

Job Location _____

Approval _____

Engineer _____

Contractor's P.O. No. _____

Approval _____

Representative _____

Model

PWSYS-FLT-STD2-LCV

Under Counter Water Filtration System

The 2-Stage LCV drinking water system produces high-quality, fresh water on demand by reducing unwanted tastes and odors from your incoming water supply. This system was designed for the Home, RV and Marine Industry where space is at a premium and quality water is essential.

Features

- 2-Stages of Filtration
 - Stage-1: Sediment filter removes particulates down to 5 micron
 - Stage-2: 1-Micron Carbon Block Filter reduces lead, cysts and VOCs (Cysts include: cryptosporidium, toxoplasma, giardia, and entamoeba)
- Adapt-A-Valve™ for easy installation
- Elegant Chrome long reach faucet included

Versatility

- Space saving design installs under sink or in limited spaces
- Adapt-A-Valve™ easily connects to water source
- Works in low-pressure applications
- Installs in minutes

Reliability

- Advanced design uses unique technology and high-quality components to ensure years of continuous trouble-free operation.
- As with all products in the Watts family, the LCV is backed by our reputation of excellence.

PURE WATER



PWSYS-FLT-STD2-LCV

Performance and Benefits

- Reduces chlorine taste and odors, lead, cysts, and VOCs (Cysts include: cryptosporidium, toxoplasma, giardia, and entamoeba).
- Ideal for home, RVs and boats
- Includes dedicated faucet and can be connected to any cold water line
- System goes well beyond basic water filtration and typical "pitcher" or "end-of-tap" filter.

Note: Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used on disinfected waters that may contain filterable cysts.

System Specifications

Operating Temperatures: Minimum 40°F (4.4°C),
Maximum 100°F (37.8°C)

Operating Pressure: Minimum 20psi (1.40 kg/cm2),
Maximum 100psi (7.03 kg/cm2)

pH Parameters: Minimum 5, Maximum 10

Flow Rate: 0.5 gpm @ 60 psig

Unit Dimensions: Approx. 11" W x 14.5" H x 5.5" D

Weight: 5 lbs.

Performance

CERTIFIED FOR	% OF REDUCTION
Cysts	99.95
Cryptosporidium	99.95
Entamoeba	99.95
Giardia	99.95
Toxoplasma	99.95
VOC's	95.00
Lead	96.00
Chlorine	98.00

Replacement Filters Packs

MODEL	FREQUENCY	DESCRIPTION
PWFIL-SED-STD-10-DEP	6 Months	5-micron sediment filter
PWFIL-CB-STD-10-1M-LCV	6 Months	1-micron carbon block filter

Note: Water conditions may require more frequent cartridge replacement

For more information please contact your authorized Watts representative.



A Watts Water Technologies Company

ES-WQ-PWSYS-FLT-STD2-LCV 1136



USA: North Andover, MA • Tel. (800) 224-1299 • www.watts.com
Canada: Burlington, ON • Tel. (888) 208-8927 • www.wattscanada.ca

© 2011 Watts