

For Commercial Applications

Job Name _____

Contractor _____

Job Location _____

Approval _____

Engineer _____

Contractor's P.O. No. _____

Approval _____

Representative _____

Model PWSYS-RO-KC4

Kwik-Change™

Reverse Osmosis (RO) Systems

Flow Rate: Up to 60 gallons per day (227 lpd)

The Kwik-Change™ Reverse Osmosis (RO) System produces up to 60 gallons per day of high-quality water that exceeds the quality of most bottled waters.

Features

- Kwik-Change™ cartridges are the fastest changeable cartridges on the market
- ¼-turn Pivot filter makes for ease of accessibility and filter change, reduces the amount of tube connections for greater reliability and less potential leaks
- Proprietary cartridges connect to (and disconnect from) the unit by a simple ¼ turn
- Space saving design installs under sink or in limited space
- Adapt-A-Valve™ easily connects to water source for ¾" compression or ½" NPT
- Automatic shutoff – No need to shutoff incoming supply when changing filters
- Top mount designer faucet installs top side and provides a ¾" high-flow water delivery system
- Air Gap faucet meets local plumbing codes
- 3-Gallon water storage holding tank
- Additional faucet finishes available

Performance

Removes harmful contaminants including:

- | | | |
|-------------------------|-------------------|--------------------------------|
| • Arsenic | • Cysts | • Nitrite |
| • Barium | • Cryptosporidium | • Perchlorate |
| • Cadmium | • Entamoeba | • Radium 226/228 |
| • Chromium (Hexavalent) | • Flouride | • TDS (Total Dissolved Solids) |
| • Chromium (Trivalent) | • Giardia | • Turbidity |
| • Copper | • Lead | • Toxoplasma |
| | • Nitrate | |

PURE WATER



PWSYS-RO-KC4

System Specifications

Temperature: Minimum 40°F (4.4°C),
Maximum 100°F (37.8°C)

Pressure: Minimum 20psi (1.4kg/cm²)
Maximum 85psi (6 kg/cm²)

pH: Minimum 2, Maximum 11

Iron (Fe): N/A Max 1.0 ppm

TDS (Total Dissolved Solids): N/A Max 1800 ppm

Hardness: N/A Max <1 grain

Unit Dimensions: Approx. 12" W x 15" H x 4" D

Replacement Filter Pack

MODEL	FREQUENCY	DESCRIPTION
PWFIL-2PACK-KC-KC4	6 Months	Includes sediment and pre-carbon filters only
PWFIL-4PACK-KC-KC4		Includes all filters and membrane
PWFIL-MEM-KC-60GPD	2 - 5 years	60 gallon per day membrane
PWFIL-GAC-KC-13	Annually	GAC final filter

Note: Water conditions may require more frequent cartridge replacement

Note: Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used on disinfected waters that may contain filterable cysts.

Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.



USA: North Andover, MA • Tel. (800) 224-1299 • www.watts.com

Canada: Burlington, ON • Tel. (888) 208-8927 • www.wattscanada.ca

ES-WQ-PWSYS-RO-KC4 1122

WATTS®

A Watts Water Technologies Company

© 2011 Watts