

For Residential and Light Commercial Applications

Job Name _____

Contractor _____

Job Location _____

Approval _____

Engineer _____

Contractor's P.O. No. _____

Approval _____

Representative _____

Model PWSYS-UF-KC3 Kwik-Change™ Ultra Filtration Membrane Water Filtration System

Features

- Equipped with long reach faucet for easy fill
- Kwik-Change™ cartridges are the fastest changeable cartridges on the market (30-second filter changeout process)
- ¼-turn pivot filter head makes for ease of accessibility and filter change, reduces the amount of tube connections for greater reliability and reduces leak potential
- Cartridges connect to and disconnect from the unit by a simple ¼-turn
- Space saving design installs under sink or in limited space
- Double Seal O-Ring cartridges ensure system integrity
- No storage tank needed
- Requires only normal line pressure to operate
- Dispenses a continuous supply of water
- Requires minimal maintenance and will provide years of clean, safe, great-tasting water

Reliability and Performance

- Advanced design uses unique technology and high-quality components to ensure years of continuous operation with trouble-free performance
- The Kwik-Change™ System water quality output exceeds the purity of other filtration and faucet mount devices

Performance

Tested	% of Reduction
Cysts	99.95
Cryptosporidium	99.95
Entamoeba	99.95
Giardia	99.95
Toxoplasma	99.95
Chlorine	98.00

PURE WATER



PWSYS-UF-KC3

Specifications

- Stage 1:** Sediment Filter removes particles down to 5 micron
- Stage 2:** Carbon Block Filter removes objectionable taste, chlorine taste, and odors
- Stage 3:** UF Membrane consists of a bundle of ultrafiltration membranes that are a physical barrier to particles, suspended solids, turbidity, most colloids, and impurities as small as 0.25 microns
- Adapt-A-Valve™ easily connects to water source
- Automatic shutoff valves in the manifold, therefore, no need to shut off the incoming water supply when changing out the filters
- Proprietary sanitary filter cartridges eliminate water spills during cartridge replacement

Note: Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used on disinfected waters that may contain filterable cysts.

System Specifications

Temperature: Minimum 40°F (4.4°C),
Maximum 100°F (37.8°C)

Pressure: Minimum 20psi (1.4kg/cm²)
Maximum 85psi (6 kg/cm²)

pH: Minimum 2, Maximum 11

Rated Capacity: 2000 Gal. (7570 liters)

Unit Dimensions: Approx. 10" W x 15" H x 4" D

Replacement Filter Packs

MODEL	FREQUENCY	DESCRIPTION
PWFIL-2PACK-KC-KC4	6 Months	Includes sediment and carbon pre-filter only
PWFIL-3PACK-KC-UF	Annual	Includes all filters and UF membrane

Note: Water conditions may require more frequent cartridge replacement



A Watts Water Technologies Company

ES-WQ-PWSYS-UF-KC3 1141



USA: North Andover, MA • Tel. (800) 224-1299 • www.watts.com
Canada: Burlington, ON • Tel. (888) 208-8927 • www.wattscanada.ca

© 2011 Watts